

## SPECIFICATION ABOUT FORNA CORK FLOORING

	<b>Cork floating flooring</b>	<b>Glue-down cork tile</b>
<b>Description</b>	Cork floating floor with UNILIN click system	cork glue-down tile
<b>Dimension</b>	36" x 12" approx. (915mm x 305mm)	24" x 12" approx. (600mm x 300mm) 12" x 12" (305mm x 305mm)
<b>Thickness</b>	Thickness: 7/16" approx. (11mm)	approx. 3/16" (4mm) or (4.8mm)
<b>Composition</b>	Top cork layer: 3mm (nominally 1/8") Middle HDF: 7mm Bottom cork underlay for sound isolation: 1mm	Natural cork with polyurethane binder
<b>Density Cork</b>	Wear layer 450-500 or 500-550kg/m <sup>3</sup> (28-30lb/fts or 30-34lb/ft <sup>3</sup> )	Wear layer 450-500 or 500-550kg/m <sup>3</sup> (28-30lb/fts or 30-34lb/ft <sup>3</sup> )
<b>Surface Finishing</b>	Prefinished with 3 coats of water-based PU varnish	Prefinished with 3 coats of durable PU varnish
<b>Sound absorption</b>	approx. 14dB	approx. 14dB
<b>Thermal resistance</b>	approx. 0.129m <sup>2</sup> K/W	approx. 0.129m <sup>2</sup> K/W
<b>Light fastness</b>	Pale in sunlight	Pale in sunlight
<b>Wear resistance</b>	with the Taber Abrasion method – Wheels CS17, load 1000g	with the Taber Abrasion method – Wheels CS17, load 1000g
<b>Packing</b>	7 planks per pack or 1.9535 M <sup>2</sup> 48 packs per pallet	(600mm x 300mm x 4mm) 11 pcs per pack or 1.98M <sup>2</sup> 4 packs per carton 54 cartons per pallet

**Storage**

**Planks must be stored horizontally**