

# SPC RIGID CORE VINYL

## POST INSTALLATION MAINTENANCE

---

- Use rosin paper and cover installed flooring area to prevent damage from other trade works. Do not use plastic film or other non-breathing material.
- Routinely vacuum, sweep and/or dust flooring.
- For heavier cleaning use a damp mop and clean water or neutral pH-based cleaner. Do not use harsh cleaners nor chemicals on flooring. Oil and petroleum-based products can result in surface staining. Do not use abrasive scrubbing tools or vacuums with beater bar. Do not use electric brooms.
- To protect flooring surface, close blinds and/or drapes during peak sunlight hours. Excessive heat and light will subject flooring to thermal degradation and potential fading effects. AVOID DIRECT SUNLIGHT EXPOSURE. Place mats at all entrances to keep dirt and debris off flooring. Use non-staining, breathable mats. Rubber mats may discolor flooring. Use floor protectors for furniture. Non-staining felt pads can be used provided they are changed on a regular basis to prevent dirt, debris and sand buildup. Wide, non-staining casters at least 2" in diameter or floor protectors should be used on rolling furniture such as office chairs. To prevent point loads on heavy furniture, use large non-staining surface floor protectors. Do not use ball type castors as they can damage floors.
- When moving heavy furniture or appliances, place a sheet of Masonite or plywood under the piece being moved to distribute the weight and reduce denting or scratching. For light pieces use a clean blanket or a piece of carpet face down under the piece to be moved. Be aware of any sharp edges as they can scratch and gouge your floor's surface.