



FLOATING
high comfort
floating floor



Acoustic Embossed
Wearlayer
Design Film
Comfort Cork Backing
High-density Fiberboard
Cork Granulate Underlayment

**Quality and comfort
at a higher level.**

FLOATING	NATURA	
Dimensions EN 427	1200 X 210 mm	
Thickness EN 428	10,8 mm	
Squareness EN 427	< 0,3 mm	
Straightness EN 427	< 0,2 mm	
Opening between panels EN 14085	< 0,1 mm	
Residual Indentation EN 433	< 0,16 mm	
Dimensional Stability EN 434	< 1,5 %	
Fire classification EN 13501-1	Efl	
Formaldehyde emission EN 717-1/2	E1	
Impact Noise Reduction ISO 140-8	18 dB	
Microscratch resistance according to EN16094:2012	MSR-A2	
Anti slip properties DIN 51130	R10	
Abrasion resistance according EN15468:2013 annex a	7500 revolutions	
Locking strength ISO 24336:2005	Short side joints 3.1kN/m	Long side joints 2.7kN/m
Castor chair test EN 425	no visible change / damages	
Effect of furniture leg EN 424:2002	no visible change / damages	
Resistance against staining EN438:2	Acetone: grade 5	Coffee: grade 5
	NaOH: grade 5	H2O2: grade 5
		Shoe polish: grade 5

